AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1.   (Original) A development method in which, while stirring a developer which is a mixture of a magnetic carrier and a toner and supplying the toner of the developer, a toner density TD (%) of the developer is measured, and the toner is supplied to the developer, depending on a reduction in the measured toner density TD (%), wherein

the toner is supplied to the developer so that the measured toner density TD (%) falls within a range specified by:

$$TD \leq \{\gamma t \bullet Vt/Nt/(\gamma c \bullet Vc)\} \times 100 \quad (1)$$

$$Vt = (/6) \bullet (Dtav\_pop)^3$$

$$Sc = \bullet (Dcav\_pop + Dtav\_pop)^2$$

$$Nt = Sc/[(3^{0.5}/2) \bullet (Dtav\_pop)^2]/2$$

$$Vc = (/6) \bullet (Dcav\_pop)^3$$

where a number average diameter of the magnetic carrier is represented by Dcav_pop (µm), a number average diameter of the toner is represented by Dtav_pop (µm), a specific gravity of the magnetic carrier is represented by γc, and a specific gravity of the toner is represented by γt.

2.   (Original) A development method in which, while stirring a developer which is a mixture of a magnetic carrier and a toner and supplying the toner of the developer, a toner density TD (%) of the developer is measured, and the toner is supplied to the developer, depending on a reduction in the measured toner density TD (%), wherein

1067935

the toner is supplied to the developer so that the measured toner density TD (%)

falls within a range specified by:

$$TD \leq \{\gamma t \cdot Vt/Nt/(\gamma c \cdot Vc)\} \times 100 \quad (2)$$

$$Vt = (/6) \cdot (Dtav\_vol)^3$$

$$Sc = \cdot (Dcav\_vol + Dtav\_vol)^2$$

$$Nt = Sc/[(3^{0.5}/2) \cdot (Dtav\_vol)^2]/2$$

$$Vc = (/6) \cdot (Dcav\_vol)^3$$

where a volume average diameter of the magnetic carrier is represented by

Dcav_vol (µm), a volume average diameter of the toner is represented by Dtav_vol

(µm), a specific gravity of the magnetic carrier is represented by γc, and a specific

gravity of the toner is represented by γt.

3.   (Original) A development method in which, while stirring a developer which is a

mixture of a magnetic carrier and a toner and supplying the toner of the developer, a

toner density TD (%) of the developer is measured, and the toner is supplied to the

developer, depending on a reduction in the measured toner density TD (%), wherein

the toner is supplied to the developer so that the measured toner density TD (%)

falls within a range specified by:

$$TD \leq [5.1(Dcav\_vol)^{-1.17}] \times 100 \quad (3)$$

where a volume average diameter of the magnetic carrier is represented by

Dcav_vol (µm), and a volume average diameter of the toner is 5.5 (µm).

4.   (Original) A development method in which, while stirring a developer which is a mixture of a magnetic carrier and a toner and supplying the toner of the developer, a toner density TD (%) of the developer is measured, and the toner is supplied to the developer, depending on a reduction in the measured toner density TD (%), wherein

the toner is supplied to the developer so that the measured toner density TD (%) falls within a range specified by:

$$TD/(Dtav\_vol)^{1.2} \leq [5.1(Dcav\_vol)^{-1.17}/5.5^{1.2}] \times 100 \quad (4)$$

where a volume average diameter of the magnetic carrier is represented by Dcav_vol (μm), and a volume average diameter of the toner is represented by Dtav_vol (μm).

5.   (Currently Amended) The development method according claim 1, wherein the toner is a toner produced by a pulverizing method.

6.   (Currently Amended) The development method according to claim 1, wherein the toner has a diameter distribution with a standard deviation σ of 15 (%) or more.

7.   (Currently Amended) The development method according to claim 1, wherein the toner has a pigment concentration of 5 (%) or more.

8.   (Original) A development apparatus in which a developer which is a mixture of a magnetic carrier and a toner is stirred and the toner of the developer is supplied, comprising detecting means for measuring a toner density TD (%) of the developer and

1067935

supplying means for supplying the toner to the developer, depending on a reduction in the measured toner density TD (%), wherein

the supplying means supplies the toner to the developer so that the measured toner density TD (%) falls within a range specified by:

$$TD \leq \{\gamma t \cdot Vt/Nt/(\gamma c \cdot Vc)\} \times 100 \quad (1)$$

$$Vt = (/6) \cdot (Dtav\_pop)^3$$

$$Sc = \cdot (Dcav\_pop + Dtav\_pop)^2$$

$$Nt = Sc/[(3^{0.5}/2) \cdot (Dtav\_pop)^2]/2$$

$$Vc = (/6) \cdot (Dcav\_pop)^3$$

where a number average diameter of the magnetic carrier is represented by Dcav_pop (μm), a number average diameter of the toner is represented by Dtav_pop (μm), a specific gravity of the magnetic carrier is represented by γc, and a specific gravity of the toner is represented by γt.

9.   (Original) A development apparatus in which a developer which is a mixture of a magnetic carrier and a toner is stirred and the toner of the developer is supplied, comprising detecting means for measuring a toner density TD (%) of the developer and supplying means for supplying the toner to the developer, depending on a reduction in the measured toner density TD (%), wherein

the supplying means supplies the toner to the developer so that the measured toner density TD (%) falls within a range specified by:

$$TD \leq \{\gamma t \cdot Vt/Nt/(\gamma c \cdot Vc)\} \times 100 \quad (2)$$

$$Vt = (/6) \cdot (Dtav\_vol)^3$$

- 6 -

$$Sc = \overline{}\bullet(Dcav\_vol+Dtav\_vol)^2$$

$$Nt = Sc/[(3^{0.5}/2)\bullet(Dtav\_vol)^2]/2$$

$$Vc = (/6)\bullet(Dcav\_vol)^3$$

where a volume average diameter of the magnetic carrier is represented by Dcav_vol (μm), a volume average diameter of the toner is represented by Dtav_vol (μm), a specific gravity of the magnetic carrier is represented by γc, and a specific gravity of the toner is represented by γt.